



RP76II 76mm Impact Receipt Printer



1. 4.4 lines/s high printing speed, support various language

2. Exquisite design, easy to use

3. Multiple interfaces optional, USB + Serial, USB + Parallel, USB + Serial + Ethernet

4. Support black mark printing, compatible with ESC/POS

5. Cutter optional, support double color printing



Print	Printing Method	9 pins serial impact dot matrix	
	Printing Speed	4.4lines/sec	
	Printing density	210 dots(whole dots)/420 dots (half dots)	
	Effective Printing Width	42CPL(7X9)/35CPL(9X9); 40CPL(7X9)/33CPL(9X9)	
Detection Method	Paper out alarm	Support	
	Overheat protection	Support	
	Black mark printing	Support	
Interface		USB, Serial, Parallel, Ethernet	
Drawer port		1 port, DC24V, 1A, 6 line RJ-11 socket	
Reliability	MCBF	9,000,000 lines	
Power Supply	DC power supply	Input DC 24V/2.5A	
Ribbon	Ribon cassette	ERC-39 color: purple/ black/ red and black double ribbon	
Printing Paper	Paper type	High quality 1 layer ordinary continuous paper or 2-3 layers copy p	
	Paper width	76±0.5 mm	
	Paper Thickness		Single-layer paper thickness:0.06-0.085mm
			Multi-layer paper thickness: 0.05-0.08mm
			Total thickness <0.20mm
	Paper roll diameter	Φ75 mm (Outside Diameter); φ12 mm (Inside Diameter)	
	Paper loading way	Not easy loading, with auto feeding function	
Paper cutting way	Manual tearing or auto cut		
Physical	Operating Temperature (°C)	0 to 45	
	Operating Humidity (%)	20 to 90 (relative humidity)	
	Storage Temperature (°C)	-100 to 60	
	Storage Humidity (%)	10 to 90 (relative humidity)	
Dimension	Outer size(L x W x H)	251x160x138 (mm)	
Application	Restaurants, Department Stores, Kitchens, Convenience Stores, Specialty Retailers, Super markets		